

Product data sheet

Specifications



Terminal block - 125 A - 14 holes

14979



Main

Range	Prisma
Product or component type	Terminal block

Complementary

[In] rated current	125 A
[Ui] rated insulation voltage	500 V
Number of terminal blocks	1 (screw) with 14 outgoers
Distribution block outgoers	1 x 35 mm ² 7 x 10 mm ² 6 x 16 mm ²
Range compatibility	Prisma G Opale Pragma

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	63.0 g
Package 1 Height	3.5 cm
Package 1 width	11.5 cm
Package 1 Length	13.0 cm
Unit Type of Package 2	P12
Number of Units in Package 2	2000
Package 2 Weight	145.2 kg
Package 2 Height	80.0 cm
Package 2 width	80.0 cm
Package 2 Length	120.0 cm
Unit Type of Package 3	S04
Number of Units in Package 3	250
Package 3 Weight	16.653 kg
Package 3 Height	30.0 cm

Package 3 width	40.0 cm
Package 3 Length	60.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------