

SOLID ABS 3819 18 G



Sample photo

Order symbol: ABS 3819 18 G
Product nbr: 5880371
Description: Enclosure, ABS
Remarks: Grey cover

EAN: 6418074039057
EI. number:
 Finland: 3423761
 Electric No. Italy: 7410135
 Electric No. Sweden: 2539715

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

| Dimensions: | | | | Accessories: | |
|-------------------------------------|----------------------|-------|--------|--|-------------------------|
| | Length | Width | Height | | |
| mm: | 378 | 188 | 180 | EKMXT | Mounting plate isolated |
| inch: | 14.9 | 7.4 | 7.1 | EKV 12 | DIN-35 Mounting rail |
| | | | | EKV 32 | DIN-35 Mounting rail |
| | | | | EKMZR | Extension frame |
| Materials: | | | | Rating: | |
| Material: | ABS | | | Ingress Protection (EN 60529): IP66/IP67 | |
| Base colour: | RAL 7035 -light grey | | | Impact Resistance (EN 62262): IK08 | |
| Cover screws material: | Polyamide | | | Electrical insulation: Totally insulated | |
| Cover colour: | RAL 7035 -light grey | | | Halogen free (DIN/VDE 0472, Part 815): 1 | |
| Cover screws colour: | Grey | | | Flammability Rating: UL 94 HB | |
| Gasket material: | Polyurethane | | | Glow Wire Test (IEC 695-2-1) °C: 650 | |
| | | | | NEMA Class: NEMA 1, 4, 4X, 6, 12, 13 | |
| Temperatures: | | | | Certificates: | |
| Temperature °C (short term): | -40 ... 80 °C | | | SGS Fimko | |
| Temperature °C (continuous): | -40 ... 60 °C | | | | |
| Temperature °F (short term): | -40 ... 175 °F | | | | |
| Temperature °F (continuous): | -40 ... 140 °F | | | | |
| Accessories: | | | | | |
| EKMVT | Mounting plate | | | | |

