

# ROLLED

Weatherproof IP68 luminaire with high impact resistant polycarbonate tube (IK10) ideal for industrial applications with dusty and wet conditions.

- Refrigeration rooms
- Food Industry
- Pools
- Bridges



850°C IK10 IP68 RoHS NO SELV

[lighting@demesne.ie](mailto:lighting@demesne.ie)



Electrical Control, Switchgear  
& Energy Saving specialists



**ROLLED****MATERIAL**

Housing: Coextruded polycarbonate tube with clear and opal sections, thickness 2mm  
 End caps: Stainless steel  
 Gear tray: White laquered steel sheet  
 Gasket: Neoprene IP68  
 Fast connector: 3-pole Wieland, plug included

**LED-SYSTEM & CONTROL GEAR**

LED module SAMSUNG  
 Mid-power LEDs  
 4,000°K neutral white  
 50,000h product life [L70]  
 Ra > 80  
 Electronic LED driver

**MOUNTING ACCESSORIES**

Stainless steel fast fixing bracket kit for ceiling or suspended mounting included.

**PRODUCT OPTIONS**

- Through wiring 3x1.5mm<sup>2</sup>; 3x2.5mm<sup>2</sup>

**ACCESSORIES**

Steel wire 2m with end stop (10039594)





Power supply: 700mA  
 Rated voltage: 220-240V  
 Frequency: 0/50-60Hz  
 Ta: -20° to 35°C




2m steel wire suspension  
with end stop

10039594

Description	Consumption	Efficiency	Luminous Flux	LOR
ROLLED 1x0.6 1,800 lm ET PC	21 W	86 lm/W	1,800 lm	80
ROLLED 1x1.2 3,600 lm ET PC	36 W	100 lm/W	3,600 lm	80
ROLLED 1x1.5 4,500 lm ET PC	44 W	103 lm/W	4,520 lm	81

Description	Code	L	D		 L x W x H (mm)	 KG	 EuroPallet
ROLLED 1x0.6 1,800 lm ET PC	10118895	644	550	1	600x100x100	2.0	270
ROLLED 1x1.2 3,600 lm ET PC	10118896	1244	1150	1	1200x100x100	3.2	135
ROLLED 1x1.5 4,500 lm ET PC	10118897	1544	1450	1	1500x100x100	3.5	135



lighting@demesne.ie



Electrical Control, Switchgear  
& Energy Saving specialists